Landsat data continuity: advanced radiometric characterization and product development

By Dennis Helder

Landsat Science Team Meeting Washington, D.C.

December 12, 2012

South Dakota State University
Image Processing Lab

SDSU Image Processing Lab

- Purpose: Radiometric, Geometric, and Spatial Characterization, Correction, and Calibration of Satellite and Airborne Imaging Systems.
- Began with a cold phone call to EROS Data Center in 1988...
- Founded in 1990
 - 1 graduate student, 1 Sun 3/80 workstation
 - 12-15 working in the lab these days

Landsat data continuity: advanced radiometric characterization and product development

- Landsat data continuity—entering the Landsat
 8 era with new spectral opportunities
- Vicarious calibration using Pseudo Invariant
 Calibration Sites (PICS): trending and absolute
- Landsat data continuity—improving the historical record's calibration




Objective: Seamless data continuity from Landsat 7 to Landsat 8


- Spectral bands—similar but different, less atmospheric influence
- New calibration opportunities

LANDSAT DATA CONTINUITY—ENTERING THE LANDSAT 8 ERA WITH NEW SPECTRAL OPPORTUNITIES







OLI, ETM+ RSRs and spectral transmittance profiles




OLI NIR band avoids water vapor absorption feature



Cirrus Band



SWIR channels




Objective: Improved vicarious calibration—both relative and absolute

- Higher precision and accuracy
- Complements onboard systems

VICARIOUS CALIBRATION USING PSEUDO INVARIANT CALIBRATION SITES (PICS): TRENDING AND ABSOLUTE



Temporal Trend of L7 ETM+ over Libya 4



Uncertainties		
Band 1	1.94%	
Band 2	1.44%	
Band 3	0.95%	
Band 4	1.83%	
Band 5	1.61%	
Band 7	2.75%	


	t-test on the slope			
	Bands	Slope	p-value	Remark
	Band 1	-1.5E-06	<0.0001	Reject
	Band 2	-3.90E-07	0.239	Fail to Reject
	Band 3	-4.81E-07	0.099	Fail to Reject
ık	Band 4	-1.89E-06	0.004	Reject
ge	Band 5	-2.97E-06	<0.0001	Reject
	Band 7	-2.86E-06	0.004	Reject

Degradation per year			
	%/yr ± 2σ		
Bands	SDSU		
1	-0.22±0.09		
2	-0.04±0.07		
3	-0.04±0.05		
4	-0.13±0.09		
5	-0.17±0.07		
7	-0.19±0.13		

Absolute Calibration: PICS-based model

- Absolute calibration can be performed by anchoring trends using a calibrated source or detector
- An empirical model was developed using Hyperion for spectral coverage and anchoring using Terra MODIS. Illumination and viewing geometries, BRDF, and atmospheric corrections were modeled.
- Validation was performed using
 Landsat 7 with accuracies of ≤2% in the
 VNIR and ~5% in the SWIR.





Days Since 1/1/1999

Objective: Adding atmospheric compensation to improve historical Landsat data calibration

- Historical calibration limited by atmospheric effects
- Use of ancillary data can improve accuracy and precision

LANDSAT DATA CONTINUITY— IMPROVING THE HISTORICAL RECORD CALIBRATION



Landsat data continuity—improving the historical record calibration

Aerosol

- Affects Bands 1,2 & 3 with decreasing intensity
- Water vapor
 - Affects Bands 5, 7 & 4
 with decreasing intensity
- Ozone
 - Affects Bands 2 and 3
 with decreasing intensity


- All Aerosol (MISR/TOMS) data ingested
 - Processing in Progress
- All NOAA data is ingested (water vapor key)
 - No further processing needed
- All OMI / TOMS Ozone ingested
 - Processing in Progress



With these 3 atmospheric effects causing most of day to day variability and affecting all bands to some level they become the key components to estimate.

Inputs – Aerosol: Example

Test case example for Aerosol from 1972 - Present



Summary/Conclusions

- Happy to be a part of the Landsat Science Team
- Looking forward to working with exceptional new and 'old' instruments
- Looking forward to working with exceptional 'new' and 'old' people, too!
- Imperative for this team to do two things:
 - Clearly proclaim the value of the Landsat mission
 - Provide solid science input to the long term requirements of the Landsat mission